

## INSTALLATION INSTRUCTIONS, 1984-1988 TOYOTA 4RUNNER REAR SPEAKER BRACKET



### NOTICE

Read instructions completely before installing this product. Refer back to the instructions frequently during installation.



### CAUTION

Flying Object Hazard.  
Fluid Splash Hazard.  
Wear safety glasses at all times when working on vehicle.



### WARNING

Cancer and Reproductive Harm –  
[www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)



TGI-311842

## STEP 1

If present, detach the storage panels located at the rearmost section of the rear panel. (Skip to step 5 if the rear panels are missing.)

## STEP 2

Detach push-in rivets. Carefully remove all push-in rivets securing the rear panel. Note: Exercise caution during removal to prevent breakage, especially if not replacing the panels.

## STEP 3

If starting with the driver's side, disconnect the rear light harness attached to the panel.

## STEP 4

After complete removal, the speaker brackets will be fully visible. Proceed to remove all mounting points securing the OEM speaker in place.

## STEP 5

Install the chosen speaker onto the new speaker brackets using the desired pattern and the mounting screws provided with the speaker.



## STEP 6

Disconnect the wiring from the old speaker and connect it to the new speaker.

## STEP 7

Once the new speaker is firmly in place, secure it using the three mounting points using the provided bolts and washers.

## STEP 8

Loosely hand tighten all mounting points.



## STEP 9

Tighten mounting screws. Once all screws are in place, tighten them securely to ensure a snug fit. This step will require a 10mm and 13mm sockets.



# INSTALLATION INSTRUCTIONS



## STEP 10

After completing the speaker installation, reattach the rear panel.

## STEP 11

Repeat the above steps for the opposite side of the vehicle to complete the speaker replacement process.